

Small and Medium Business, Storage, Networking, Web Hosting, and Security Appliances

Intel® Server Board S2600ST Product Family Featuring  
the 2<sup>nd</sup> Generation Intel® Xeon® Processor Scalable Family

# Flexible General-Purpose Server Board in a Standard Form Factor



## Powerful Compute, Flexible I/O, Storage and Networking Capacity

The Intel® Server Board S2600ST product family delivers robust features and powerful performance in a standard 12" x 13" EEB form factor for flexibility and ease of adoption. Featuring the 2<sup>nd</sup> Generation Intel® Xeon® Scalable processor family, high PCIe\* lane availability, and SAS/SATA/NVMe\* flexibility, it provides a cost-effective option for pedestal, rack mount or custom systems. The S2600ST is ideal for use in small and medium business, storage, networking, web hosting, and security appliances where feature capacity and price-performance balance is key.

## Standard EEB Form Factor with Flexible I/O, Storage and Networking Capacity

- Dual CPU sockets with support for the 2<sup>nd</sup> Generation Intel® Xeon Scalable processor family
- 16 DDR4 DIMM slots
- Six 3.0 PCIe\* slots, providing maximum configuration flexibility
- Up to four onboard PCIe\* OcuLink connectors for direct attach NVMe\* 2.5" SSD support
- Operating system boot option via two 80-mm M.2 connectors (x2 and x4 PCIe/SATA)
- Networking flexibility with dual 10GBase-T and dual 10G SFP+ modules
- Up to 150 Gbps high speed compression via three Intel® QuickAssist Technology (Intel® QAT) engines

## Ideal for Performance Storage, Networking, Web Hosting, and Security Appliances

The S2600ST product family is optimized for the 2<sup>nd</sup> Generation Intel® Xeon® Scalable processor family. This latest generation processor is designed for performance, with high scalability and resiliency with no I/O compromise, and supports a wide range of existing and emerging workloads. The S2600ST product family uses a number of key processor advancements:

- **Support for Intel® Speed Select<sup>†</sup>** enables the optimization of processor resources to enhance workload performance, increase utilization, and optimize TCO.
- **NVMe\* Enablement** alleviates the I/O bottleneck with high performance and capacity.
- **Integrated 10G Ethernet with RDMA** eliminates TCP/IP overhead by offloading transport to NIC for faster switching and packet filtering.
- **Intel® Virtual RAID on CPU (Intel® VROC)** enables high- performance, highly scalable CPU-based RAID with NVMe, with high IOPS and low latency.

† On supported 2nd Generation Intel® Xeon® Scalable processors

## Built with Intel® Quality, Reliability and Performance

Intel® Server Products are backed by Intel's design excellence and manufacturing expertise to deliver processing power with high levels of flexibility, manageability and reliability. Product and design quality is paired with 3-year standard warranties and robust technical and incident resolution support to ensure customer satisfaction.



## Flexible, Feature Rich, Powerful, and Cost-Effective

Intel® Server Board S2600ST is available in two feature-optimized family SKUs:

- **S2600STBR** – Base SKU, including dual 10GbE integrated LAN ports
- **S2600STQR** – Integrated Intel® QAT support for bulk cryptography, public key cryptography, and up to 150 Gbps high speed compression

### Common use cases:

- Powerful small and medium business servers
- Purpose-built appliances for networking, telecommunications, storage and security
- Web hosting and virtualization

## INTEL® SERVER BOARD S2600ST PRODUCT FAMILY SPECIFICATIONS

SERVER BOARD SPECIFICATION	DETAILS
Board SKUs	S2600STBR, S2600STQR
Board Dimensions	12" x 13" SSI EEB form factor
Intel Processor	2 <sup>nd</sup> Generation Intel® Xeon® Scalable processor family (Platinum, Gold, Silver, and Bronze)
Processor Socket Type	Two Socket-P LGA3647
Maximum Processor TDP	205W
Intel Chipset	<ul style="list-style-type: none"> <li>• Intel® C624 Chipset – S2600STBR</li> <li>• Intel® C628 Chipset – S2600STQR</li> </ul>
Max DIMM slots	16 DIMMs Total - six channels per processor, 2-1-1 configuration
Memory Type	DDR4 RDIMMs or LRDIMMs
Memory Capacity	Up to 1.0 TB for Gold/Platinum CPUs, 512 GB for Silver/Bronze CPUs
Memory Speed <sup>1</sup>	2933 MT/s @ 1 DPC, 2666 MT/s @ 1 DPC and 2 DPC (DPC = DIMMs per channel)
Memory Voltage	1.2V, DDR4 Standard I/O voltage
Video	Integrated 2D video controller with 128MB DDR4 memory
Networking	<ul style="list-style-type: none"> <li>• Dual onboard 10GBase-T ports</li> <li>• Dual SFP+ via optional accessory riser card</li> </ul>
Intel® QuickAssist Technology	Supported on S2600STQR
TPM Support	One connector for optional TPM 2.0 module
Board Weight	1.5 kg (3.31 lbs.)
Packaging Dimensions	Single Pack: 460(L) x 376(W) x 108(H) mm Bulk Pack: 586(L) x 464(W) x 480(H) mm (10 boards per pack)
Packaging Dimensions	0.87 kg (single pack), 5.2 kg (bulk pack)
Warranty	3-year limited warranty



I/O CONNECTORS	DETAILS
USB	Two external USB 3.0 ports Two external USB 2.0 ports One internal Type-A USB 2.0 port One internal 20-pin connector for optional 2x USB 3.0 port front panel support
Serial	One internal DH-10 Serial-A port header for optional rear serial port support
Video	One DB-15 VGA external connector
Front Panel SSI-EEB	One 2x15 pin SSI-EEB compliant front panel header
Storage	Two single port 7-pin SATA 6 Gbps connectors
	Two 4-port SATA Mini-SAS HD Connectors
	Two 80-mm M.2 connectors (x2 and x4 PCIe* & SATA)
	PCIe* OCuLink* connectors for direct attach NVMe* 2.5" SSDs • 4 connectors – S2600STBR • 2 connectors – S2600STQR
Network	Two integrated 10GbE Ports

EXPANSION OPTIONS	DETAILS
PCIe* Add-in Card Support	Six PCIe* slots with support for up to six PCIe 3.0 add-in cards – See product TPS (Use of all PCIe slots requires dual processors populated.)
LAN Riser	SFP+ card for onboard Ethernet/Fiber controller physically aligned to Slot 5

SERVER MANAGEMENT & SECURITY FEATURES	DETAILS
Embedded Server Management Features	Integrated Baseboard Management Controller, IPMI 2.0 compliant Dedicated RJ45 1GbE server management port Includes Standard Server Management Features – See product TPS Support for Intel® Server Management Software
Advanced Server Management Features	Support for Intel® Remote Management Module 4 Lite accessory option enabling Integrated KVM and Remote Media Redirection
Intel® Transparent Supply Chain	Includes Statement of Conformance and Platform Certificate



# INTEL® SERVER CHASSIS P4000 SPECIFICATIONS

SERVER BOARD SPECIFICATION	DETAILS
Type	Pedestal chassis, optional 4U rack mount
Max Processor TDP	Up to 205 W depending on configuration
Chassis Dimensions	17.24" x 6.81" x 24.9" (438 x 173 x 612 mm)
Packaging Dimensions	825 x 610 x 370 mm
Server Board Support	Intel® Server Board S2600ST product family (not included)
Power Supply Options	IP4304XXMFEN2: single non-redundant 550 W PSU included P4304XXMUXX: supports redundant 750 W or 1600 W PSU (not included)
System Fan Support	P4304XXMFEN2: Two 120 x 38 mm non-redundant fans P4304XXMUXX: Five 80 x 38 mm redundant hot-swap fans

EXPANSION OPTIONS	PCIe* SOURCE	DETAILS
PCIe Slot 1	CPU1	x8 PCIe* Gen 3 electrical and mechanical
PCIe Slot 2	CPU1	x16 PCIe Gen 3 electrical and mechanical (riser capable)
PCIe Slot 3	CPU1	x8 PCIe Gen 3 electrical and mechanical
PCIe Slot 4	CPU1	x16 PCIe Gen 3 electrical and mechanical
PCIe Slot 5	CPU0	x8 PCIe Gen 3 electrical and mechanical
PCIe Slot 6	CPU0	x16 PCIe Gen 3 electrical and mechanical (riser capable)
LAN Riser	CPU0	SFP+ card for onboard Ethernet/Fiber controller physically aligned to Slot 5

PCIe Gen 3.0 unless noted. Use of all PCIe slots requires dual processors populated.

STORAGE	TOTAL # OF DRIVES	TYPE
Front Peripheral Bays	Three at 5.25" half-height	Half-height drive bays for CD/DVD-ROM or tape drives Can be used as one 3.5" removable media drive bay
Fixed Drive Support	Four at 3.5" or 2.5"	Up to four 3.5" or 2.5" fixed SATA drives, cabled SAS drives not supported
LAN Riser	CPU0	SFP+ card for onboard Ethernet/Fiber controller physically aligned to Slot 5

ADDITIONAL STORAGE OPTIONS	TOTAL # OF DRIVES	TYPE
Hot-Swap Drive Bay AUP4X35S3HSDK	Eight at 3.5" or 2.5"	4x3.5", two per system, also supports 2.5"
Hot-Swap Drive Bay AUP8X25S3DPDK	16 at 2.5"	8x2.5", two per system, dual-port SAS
Hot-Swap Drive Bay AUP8X25S3NVDK	16 at 2.5"	8x2.5", two per system, combo drive bay Note: P4000 chassis is limited to four NVMe* SSDs
SAS Expander RES3TV360	16 at 2.5"	36-port 12G SAS expander, use with 8-port Intel® RAID Adapter

Mixing of SAS/SATA/NVMe drives is permitted.

Mixing of 3.5" and 2.5" drives is supported; however, mixing of 3.5" and 2.5" drive cage upgrade kits is not supported



## INTEL® SERVER BOARD AND CHASSIS ORDER CODES

ORDER CODE	TYPE	DESCRIPTION
S2600STBR	Server Board	Server board supports two Intel® Xeon® processor Scalable family up to 165 W TDP each, 16 DIMMs, two 10Gb Ethernet ports, 6 PCIe* slots
BBS2600STBR	Server Board	10 pack of S2600STBR boards
S2600STQR	Server Board	Server board supports two 2 <sup>nd</sup> Generation Intel Xeon processor Scalable family up to 165 W TDP each, 16 DIMMs, two 10Gb Ethernet ports, 6 PCIe* slots, Intel® QuickAssist Technology (Intel® QAT)
P4304XXMFEN2	4U Pedestal Chassis	4U pedestal chassis, fixed 4x 3.5" HDD support, optimized for configurations with fixed fans and PSU
P4304XXMUXX	4U Pedestal Chassis	4U pedestal chassis, fixed 4x 3.5" HDD support, optimized for configurations with hot-swap fans, PSUs, and drives (PSUs and drive cages not included)



<sup>1</sup> The maximum memory speed supported depends on the processor used.

See Intel® Server S2600ST Product Family Configuration Guide for accessory kit and spare order codes.

For more information on Intel Server Products and Solutions visit: [intel.com/serverproducts](https://www.intel.com/serverproducts)

For more information on Intel® RAID visit: [intel.com/RAID](https://www.intel.com/RAID)

For product specifications visit: [ark.intel.com](https://ark.intel.com)

Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software, or service activation. Performance varies depending on system configuration. No computer system can be absolutely secure. Check with your system manufacturer or retailer or learn more at [intel.com](https://www.intel.com).

Software and workloads used in performance tests may have been optimized for performance only on Intel® microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information visit [intel.com/performance](https://www.intel.com/performance).

Intel, the Intel logo, and Xeon are trademarks of Intel Corporation in the U.S. and/or other countries.

\*Other names and brands may be claimed as the property of others.